



## TH115 Series

This compact, stylish thermostat comes loaded with advanced programming features and a large backlit LCD



 Print this page

### MODELS & RATINGS

TH115-A-024T	0.5 A @ 24 V	R, C, W
TH115-AF-024T	0.5 A @ 24 V	R, C, W
TH115-F-024T	0.5 A @ 24 V	R, C, W

Includes 15 ft. / 4.6 m sensor (AF, F models)

### SPECIFICATIONS

#### TEMPERATURE CONTROL

Microprocessor-optimized PIA  
Heating cycles: 15 min.  
Accuracy:  $\pm 0.5^{\circ}\text{C}$  /  $0.9^{\circ}\text{F}$

#### PROGRAMMING

7-day, 4 time periods/day, 2 temp. settings  
Pre-programmed or personalized schedule  
Early Start function  
Selectable 12- or 24-hour clock /  $^{\circ}\text{C}$  or  $^{\circ}\text{F}$

#### DIMENSIONS (H•W•D)

124 x 70 x 23 mm / 4.9 x 2.8 x 0.9 inches

### FEATURES

**A model** controls ambient temperature

**AF model** controls ambient temperature with possible limit on floor temperature

**F model** controls floor temperature

**ON/STANDBY** switch enables thermostat shutdown at end of heating season for added security

**On-screen heating power indicator** gives at-a-glance verification of power being used


**Temporary bypass** enables temperature override without changing programming


**Battery-free backup** means no re-programming your schedule after power outage

### ACCESSORIES

Aube AC112-01 North American floor sensor, 15 ft. / 4.6 m  
Aube RC840 electromechanical relay  
Aube RC840T electromechanical relay

### INSTRUCTION MANUAL

 TH115-A-F-AF-024T.pdf (format PDF)

 To view a PDF, you must have Acrobat Reader.  
Click on the icon to download it for free.

### WARRANTY

