



TH140 Series

This versatile thermostat controls systems from millivolt to 240 V



 [Print this page](#)

MODEL & RATINGS

TH140-28-01 5 A (resistive) @ 24 V, 120 V, 240 V R, W World except France
2 A (inductive) @ 24 V, 120 V, 240 V

Millivolt compatible

SPECIFICATIONS

TEMPERATURE CONTROL

PROPORTIONAL ADAPTIVE

Cycles: selectable 5, 10, 15 or 20 minutes

CONVENTIONAL WITH ANTICIPATION

Programmable temp. span: $\pm 0.3^{\circ}\text{C}$ (0.5°F) to $\pm 0.6^{\circ}\text{C}$ (1.1°F)

PROGRAMMING

7-day, up to 4 time periods, 2 temps. / day

Selectable 12- or 24-hour format, $^{\circ}\text{C}$ or $^{\circ}\text{F}$

POWER SUPPLY

2 AA batteries (not included)

DIMENSIONS (H•W•D)

126 x 97 x 26 mm / 4.9 x 3.8 x 1 inches

FEATURES

Advanced temperature control ensures total comfort by minimising temperature swings

Selectable cycles mean thermostat can be optimised to heating system

Pump protection – for hot water heating activates pump for one minute every 24 hours to prevent seizure

Armchair programming – convenient programming by removing faceplate from base

Instructions inside front panel enable quick, easy programming

Precise LCD – shows room temperature in increments of 0.1°C or 0.1°F

Low battery indicator – gives 60 days warning to replace batteries

Remote input enables change of temperature modes from phone (Aube telephone controller required) or alarm/automation system (12 VDC transformer required)

ACCESSORIES


Aube CT240 telephone controller

Aube RC840 electromechanical relay

Aube RC840T electromechanical relay

INSTRUCTION MANUAL

 TH140-28.pdf (format PDF)

 To view a PDF, you must have Acrobat Reader.
Click on the icon to download it for free.

CERTIFICATION



WARRANTY

